

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
19 February 2004 (19.02.2004)

PCT

(10) International Publication Number
WO 2004/015668 A1

- (51) International Patent Classification⁷: **G09G 3/32**
- (21) International Application Number:
PCT/IB2003/003204
- (22) International Filing Date: **22 July 2003 (22.07.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
0218172.5 6 August 2002 (06.08.2002) GB
- (71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL];**
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **CHILDS, Mark, J.**
[GB/GB]; c/o Philips Intellectual Property & Standards,
Cross Oak Lane, Redhill, Surrey RH1 5HA (GB). **FISH,**
David, A. [GB/GB]; c/o Philips Intellectual Property &
Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA
(GB).
- (74) Agent: **WILLIAMSON, Paul, L.;** Philips Intellectual
Property & Standards, Cross Oak Lane, Redhill, Surrey
RH1 5HA (GB).
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU,**
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GI,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LI, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): **ARIPO patent (GI, GM,**
KE, LS, MW, MZ, SD, SI, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: **ELECTROLUMINESCENT DISPLAY DEVICE TO DISPLAY LOW BRIGHTNESS UNIFORMLY**



(57) Abstract: An electroluminescent (EL) display device has current-driven pixels and is operable in at least two phases within each frame period. In one phase, one of a first plurality (31) of analogue drive currents can be driven through EL display element. In another longer phase, one of a second plurality (33) of analogue drive currents is independently driven through the EL display element. This device combines a time ratio method with an analogue drive scheme. A shorter phase may provide the higher resolution (smaller) increments and one longer phase may provide lower resolution (larger) increments. Low brightness outputs can be achieved with a higher drive current, but over a short duration, which reduces non-uniformity in the pixel output.

WO 2004/015668 A1